



0.75kW Centrifugal Booster Pump

- Best efficiency flow range 40 to 80lt/min
- Best efficiency pressure range 1.9 to 2.8 bar
- 1-year Quality Warranty
- NRCS approved
- Energy-efficient

- Easy to operate
- Automatic start/stop function
- Dry run protection
- Over-current protection
- Pre-wired with 3-point plug
- Brass impeller
- Stainless shaft



When choosing a pump consider your setup and what the pump will be used for.



Bathroom



Misting



Pop up



Impact



Dishwasher



Class Leading Efficiency

The 0.75kW centrifugal pump is designed to provide optimal flow while using minimal energy and is ideal for irrigation and everyday household use

Pump specifications

- Pump model: CPM158
- Motor power: 0.75kW
- Max flow: 100 lt/min
- Max pressure: 3.2 bar
- Max fluid temperature: 40 $^{\circ}\text{C}$
- Max ambient temperature: 40 °C
 Max suction lift:
- 7m
 Protection:
- IP 65
 Input voltage: 220 V
- Frequency: 50 Hz

Recommended connections

• Suction pipe:

HDPE or helical coil reinforced flexible hose (minimum 1" or 25mm)

Discharge pipe:
 Copper, HDPE or any

Copper, HDPE or any SABS approved piping (3/4" or 22mm)

Integrated functions for protection from

- Dry run
- Over-current
- Over/under voltage

Availability



Stock Item:

Stock items are subject to a 7 day calendar lead time

Packaging



Package dimensions in mm: 485(h) x 372(w) x 235(l)

Total weight: 16kg