



0.75kW Stainless Steel VSD Pump

- Best efficiency flow range 28 to 56lt/min
- Best efficiency pressure range 2 to 4 bar
- 1-year Quality Warranty
- NRCS approved
- Energy-efficient
- Solar compatible (220V)
- Low noise level
- Constant pressure
- Automatic start/stop
- Adjustable start and shut-off pressures
- Restart delay
- Auto-rotation



When choosing a pump consider your setup and what the pump will be used for.



Bathrooms



Impact Sprinklers



Pop up Sprinklers



Misting Sprinklers



Washing Machine



Dishwasher

Get the power of precision and efficiency

With ultra-low noise levels, a soft-start feature for solar efficiency, and customisable performance with adjustable pressures, our 0.75kW VSD Pump is the ultimate choice for smarter, more efficient water management.

Pump specifications

- **Pump model:** HMS750
- **Motor power:** 0.75kW
- **Max flow:** 75 lt/min
- **Max pressure:** 5.3 bar
- **Max fluid temperature:** 80 °C
- **Max ambient temperature:** 40 °C
- **Max suction lift:** 7m
- **Protection:** IP44
- **Suction size:** 25 mm/1"
- **Discharge size:** 25 mm/1"

Recommended connections

- **Suction pipe:** HDPE or helical coil reinforced flexible hose (minimum 1" or 25mm)
- **Discharge pipe:** HDPE (minimum 1" or 25mm class 6)

Integrated functions for protection from

- Dry run and over-heat
- Over- and under-voltage
- Overload and abnormal pressure

Packaging



Package dimensions in mm:
335(h) x 195(w) x 435(l)

Total weight:
14kg