



Basic Booster Pump & Connector Kit

- Best efficiency flow range
5 to 15lt/min
- Best efficiency pressure
range 1 to 2.3 bar
- 1-year Quality Warranty
- NRCS approved
- Energy-efficient
- Easy to operate
- Automatic start/stop function
- Pre-wired with a 3-point plug
- Dry running protection
- Over-heat protection



When choosing a pump consider your setup and what the pump will be used for.



Toilet



Pyramid
Sprinkler



Tap

Simplify your backup water management

Our 0.37kW Basic Booster Pump and Connector Kit is easy to install and use, and is ideal for small-scale backup solutions where pressurised water is required.

Pump specifications

- **Pump model:**
QB60 G
- **Motor power:**
0.37kW
- **Max flow:**
23 lt/min
- **Max pressure:**
3 bar
- **Max fluid temperature:**
80 °C
- **Max ambient temperature:**
40 °C
- **Max suction lift:**
7m
- **Protection:**
IPX 4
- **Input voltage:**
220 V
- **Frequency:**
50 Hz

Recommended connections

- **Suction pipe:**
HDPE or helical coil reinforced flexible hose (minimum 1" or 25mm)
- **Discharge pipe:**
Copper, HDPE or any SABS approved piping (1" or 25mm)

Integrated functions for protection from

- Dry run and over-heat

Availability



Stock Item:

Stock items are subject to a 7 day calendar lead time

Packaging



Package dimensions in mm:

202(h) x 250(w) x 322(l)

Total weight:

5.5kg